ALL MATERIALS & ALL SURFACES





DECK CAULK

Non-corrosive, high quality fast curing AST polymer sealant designed for marine applications where UV, extreme weather, long time fresh & salt water resistance and waterproof properties are required. It is especially developed for waterproof sealing of teak wood decks in nautical applications.

HIGH UV RESISTANCE

LONG TIME FRESH & SALT WATER RESISTANCE

WATERPROOF

ALL MATERIALS & ALL SURFACES





DECK CAULK

FEATURES

- · Chemically resistant to fresh water, salt water and diluted acids,
- UV. ageing, moisture and extreme weather resistance.
- Eco-friendly, free from isocyanate, solvent, acids and halogens,
- · Highly elastic in low and high tempratures,
- · Excellent primerless adhesion to numerous porous and non-porous substrates,
- · Sandable after curing,
- · Fast curing, low odor and non-sag properties.

APPLICATION AREAS

- Deck Caulk is designed for sealing of connection joints between teak decks and variety of decking substrates,
- Outstanding primerless adhesion on joining elements made from wood, concrete, plastic, steel, aluminum, zinc, copper, porcelain, ceramics, PVC, metals, polyester, polycarbonate, natural stone, marble, mirror, glass and porous surfaces.
- If using for the first time a preliminary test is recomended for plastics before application.





