



707

SHOE & LEATHER KIT

Shoe & Leather Kit is a two part special set consist of a high viscosity cyanoacrylate adhesive and activator used especially in shoe repair for bonding leather, rubber and wood.

FEATURES & BENEFITS

- **Very fast bonding,**
- **High adhesive strength**
- **Thanks to its high viscosity formula, it can be used in vertical places without pour and splash,**
- **Activator makes it possible and incredibly fast to bond even porous surfaces,**

APPLICATIONS

- **Repair of the leather, rubber, heel and stout leather parts of the shoe,**
- **Perfect company in daily life for bonding leather, rubber and wood.**

INSTRUCTIONS

- One of the substrates need to be smooth and have a good connection area.
- Apply a drop on one of the substrates and use spray on the other one.
- Join substrates and press firmly for approximately one minute.
- Application temperature is between +5°C and +35°C.

RESTRICTIONS;

- Cyanoacrylates should ideally be stored in original sealed containers until used.
- Avoid exposure to strong light and heat sources
- Cyanoacrylates can bond to skin within seconds
- Do not drip into skin or into eyes - can cause serious injury to your eyes.
- Will become hard in container if not closed properly!
- Activator is flammable. Do not throw into fire.
- Activator box is pressured. Do not crush or drill.

Incredibly
Fast Bonding
Experience



STORAGE AND SHELF LIFE;

12 months between 5 and 25 °C in closed original packaging.

PROPERTIES

Glue

Basis	: Ethyl Cyanoacrylate	
Appearance	: Liquid gel	
Color	: Colorless	
Application Temperature	: +5°C to +35°C	
Density	: 1.06 ± 0.01 gr/cm ³	ASTM D1875
Flashpoint	: > 81 ° C	
Viscosity	: 1200 - 1800 Cps at 25°C	ASTM D1084
Temperature Resistance	: -20°C to +70 °C	

Activator

Basis	: Hexane	
Appearance	: Aerosol	
Color	: Colorless	
Application Temperature	: +5°C to +35°C	
Temperature Resistance	: -20°C to +70 °C	

PRODUCT

Product Type	Volume / Weight	Package
Activator & Glue	100 mL + 25 gr	48
Activator & Glue	250 mL + 65 gr	24
Activator & Glue	500 mL + 125 gr	24

DISCLAIMER

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.