



## E80 SILICONE LUBRICANT

### 1 – DESCRIPTION

**AKFIX E80** is a silicone based mould release agent. It shows perfect performance even at very high temperatures.

### 2 – PROPERTIES

- Due to its silicone content, it provides long working life at high temperatures.
- Lubricates to reduce friction and eliminate squeaks in all, types of mechanical parts.
- The product repels water, protects and renews rubber surfaces.
- Anti-static and anti-corrosive.
- Do not leave residues.
- Not water soluble.
- Non-toxic

### 3 - APPLICATIONS

- As a cleaner and mould release agent in textile, plastic and rubber industries.
- Windshield wiper linkage
- Interior hinges, slides or springs
- Snow blower chutes.

### 4 – INSTRUCTIONS

- Remove dirt and grease from surface treated.
- Shake can thoroughly before use.
- For best results, aerosol container should be at room temperature before spraying.
- Spray on approx. 20 – 25 cm distance from the surface.
- Apply a thin layer evenly.

### 5- PACKAGING

| Product | Volume | Package |
|---------|--------|---------|
| E80     | 400ml  | 12      |

### 6- SHELF LIFE

24 Months if stored properly.



## 7- SAFETY

- Use gloves when working.
- Pressurized container. Do not expose to temperatures higher than +50 °C.
- Keep away from direct sunlight
- Do not pierce or burn, even after use.
- Keep away from sources of ignition, no smoking.
- Keep out of the reach of children

## 8- TECHNICAL PROPERTIES

|                         |                           |
|-------------------------|---------------------------|
| <b>Form</b>             | : Aerosol                 |
| <b>Appearance</b>       | : Transparent             |
| <b>Specific gravity</b> | : 0,98 gr/cm <sup>3</sup> |
| <b>Odor</b>             | : Characteristic          |
| <b>Flash Point</b>      | : N/A                     |