



# **R60 TYRE REPAIR KIT**

#### 1 - DESCRIPTION

TYRE REPAIR KIT eliminates the need for an immediate tyre change, sealing and inflating your tyre within seconds.

#### 2 - PROPERTIES

- No need for lifting- jack or any other tools.
- Finds the hole in the tyre and seals it
- Water based.
- Can be cleaned easily with the water after application
- Does not harm the tyre valve
- Instantly repairs punctured tyres, without removing the wheel
- Inflates the tyre (up to a pressure of 1,2 to 2,5 bar), so that one can immediately continue to drive at a moderate speed.
- Harmless to tyres and wheels.

### 3 - APPLICATIONS

- For cars, motorcycles, caravans and trailers.
- For tubeless tyres or tyres with inner tubes.

### 4 – INSTRUCTIONS

- Shake the spray can before use.
- Ideal processing temperature 15°C to 25°C.
- Turn the wheel until the valve is at the top.
- Completely deflate the tyre. Screw the connection of the spray can to the tyre valve. Upturn the spray can and inject the entire contents.
- It is recommended to have the tyre repaired as soon as possible. Before repair please clearly inform the tyre service that this product has been used.

#### 5 - PACKAGING

Product	Volume	Package
R60	300ml	24

#### 6- SHELF LIFE

36 months if stored properly.

08 / 2015 Rev.05 Page 1





Yeşilbayır Mah. Şimşir Sk. No: 22 Hadımköy - İstanbul/TÜRKİYE Tel: 0212 771 13 71 Fax: 0212 771 38 88 🔰 www.akfix.com - info@akfix.com

## **7-SAFETY**

- Pressurized container. Do not expose to temperatures higher than +50 °C.
- Keep away from direct sunlight and keep away from sources of ignition.
- Use only in well-ventilated areas.
- Keep out of reach of children.

## **8- TECHNICAL PROPERTIES**

Form	: Aerosol
Appearance	: Transparent
Specific gravity	: 1 gr/cm <sup>3</sup>
Odor	: Characteristic
Flash Point	: N/A
Solid content	: %50

08 / 2015 Rev.05 Page 2