



WALL REPAIR PATCH KIT

Wall Repair Patch Kit consists of ready mixed drywall repair compound with high crack filling capacity in concrete, flexible self-adhesive perforated aluminum patch, grit sandpaper and ergonomic plastic putty knife.

FEATURES & BENEFITS

- **No mixing required, easy to use,**
- **High crack filling capacity,**
- **All required equipment is in one package.**
- **Dries quickly to a hard finish,**
- **Can be varnished or painted,**
- Easy to sand, can be drilled,
- Water based non-toxic.

APPLICATION AREAS

- **Drywall Repair Kit is used to fill cracks, splits, holes and surface defects and imperfections in construction materials like wood, concrete, brick etc.**
- **Effectively repairs the concrete and plaster surfaces of walls and ceilings.**

INSTRUCTIONS

- Make sure the package is filled with its contents.
- The surface must be cleaned from all loose materials, dust, dirt, oil and any other contaminants.
- Paste the patch on the surface to be fixed and press it firmly. Make sure it sticks well.
- Spread the repair compound on the patches by using the putty knife with movement from the center to the periphery. Be sure to pour it exactly over the patch so that no voids remain.
- After the repair compound is completely dry, sand the surface for a professional smooth finish.
- For increasing the curing rate a hair dry can be used.
- In case of need the procedure can be repeated.
- The surface can be painted on demand.

One Package
is All You
Need



RESTRICTIONS

- Not suitable for use where flexibility and movement accommodation is needed.
- Do not apply onto coated surfaces.
- For external applications, it must be over coated with varnish or paint to provide water resistance.
- Various two part acid catalyzed varnishes may not adhere. Preliminary test recommended before use.
- Product may become a little dry, add a small amount of hot water and mix to a smooth paste.

STORAGE AND SHELF LIFE;

The repair compound has a shelf life of at least 18 months if stored in a cool, dry place in its original moisture-tight container. The glue should not be stored below 5°C or above 30°C. If the material is kept beyond the recommended shelf life, it is not necessarily unusable. A check should be performed to observe whether the product has separated, thickened, or shows signs of bacterial degradation (bad smell, discoloration and low viscosity).

PROPERTIES

Base	: Natural Polymer based
Curing Mechanism	: Moisture
Density	: 1.92 ± 0.04 gr/cm ³
Practical Consumption	: 0,600 Lt/m ² – (1,052 Kg/m ²)
Tack Free Time	: 5-45 min. (23 °C % 50 humidity)
Application Temp. Range	: 5°C -30°C
Viscosity	: Paste
Water Resistance	: Poor- needs to be over-coated for external applications
Drying Time	: 3 mm / 24 hours (23 °C % 50 humidity)
Paintability*	: After 1 hour
Ph	: 7.5-9

*Due to diversity of the paints, preliminary test required.

PRODUCT

Product Type	Quantity
Drywall repair compound acrylic sealant	280 ml
Flexible, self-adhesive perforated patch	10 cm x 10 cm (3,2" x 3,2")
100 Grit sandpaper	5 cm x 5 cm (2" x 2")
Ergonomic plastic putty knife	8.9cm (3.5")

DISCLAIMER

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.