



INOX SPRAY PAINT

1 – DESCRIPTION

Inox Spray Paint is designed for all lacquer finishes and repairs in the colour of stainless steel, for colour adaptations in the surrounding field of stainless steel surfaces (test the color!).

2 – PROPERTIES

- High-grade nitro-combi quality
- Very good coverage
- Excellent adhesion on many surfaces
- Good flow, smooth surface
- Suitable for indoors and outdoors applications
- Weather-resistant, light-proof, UV-resistant
- Scratch-, shock- and impact-resistant
- Resistant to engine oils, diluted cleansers etc.
- Quick-drying (The drying time depends on surrounding temperature, air humidity and thickness of the applied coat).

3 – APPLICATIONS

- For all lacquer finishes and repairs in the colour of stainless steel, for colour adaptations in the surrounding field of stainless steel surfaces (test the color!).
- Application is possible on the most undergrounds e. g. metal, wood, glass, ceramics, paper, stone etc.

4 – INSTRUCTIONS

Preparation of the ground:

- If necessary, equalize uneven surfaces (fill, sand, prime)
- The surface has to be clean, dry and free from fat.

Lacquering:

- Cover areas not to be painted.
- Before use, shake the can for 2-3 minutes.
- Test spray at an invisible spot to check colour-matching and compatibility of the lacquer.
- Spray from a distance of approx. 25 cm several thin coats.
- Do not spray over synthetic paints!

5- STORAGE AND SHELF LIFE

10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%).



6- ENVIRONMENT AND LABELLING

Environmentally sound: The products are 100% free of heavy metals. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling: All products comply with the actual labelling regulations according to

Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

7- TECHNICAL PROPERTIES

Basis	: Nitro-combi	
Color	: Stainless steel silver	
Smell	: Solvent	
Degree of gloss	: Matt: 5-10 gloss units	DIN 67530
Efficiency	: Approx. 1.2 m ² * (400 mL)	
Drying time (20 °C and 50% R.H)	: Approx. 10 minutes (Dust-dry) 30 minutes (Dry to touch) Approx. 24 hours (Cured)	
Temperature resistance	: Up to 80°C	

* Depending on consistence and color.

8- COLOR TABLE

Art No	Color Code
423215	Inox Spray

9- DISCLAIMER

This application-technological information is given to the best of our knowledge. The notes mentioned herein are ,however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. Akkim Sealants & Adhesives is not responsible for any false usage of the product.