



METAL GLOSS CHROME EFFECT

1 – DESCRIPTION

Metal Gloss Chrome Effect gives a long-term look similar to polished chrome and gold to smooth surfaces. Not weather-resistant. Not resistant to abrasion, therefore not suitable to spray on objects for daily use.

2 – PROPERTIES

- High-grade acrylic quality
- Resistant to water and common household cleansers.
- Effect of gloss can change by intense rubbing or wiping.
- Colour of contents similar to cap
- Very good coverage
- Very high gloss
- Excellent adhesion
- Good flow, smooth surface
- Quick-drying (The drying time depends on surrounding temperature, air humidity and thickness of the applied coat).

3 - APPLICATIONS

- Suitable for all smooth surfaces like metal, wood, glass and many coatable plastics.
- Indispensable for constructors of fair booths, decorators, florists etc., but also for handicrafts at home, in courses and seminars.

4 - INSTRUCTIONS

- The ground has to be clean, dry and free from rust and fat.
- Absorbent surfaces have to be primed with Universal Primer
- Mask off areas not to be painted.
- Before use, shake can for 3 minutes.
- Test spray at an invisible spot.
- Spray from a distance of 25 cm.
- Spray in 2 minute intervals several thin coats.
- Do not spray over surfaces which are painted with synthetic resin lacquer!

Important: Due to technical reasons it is not possible to conserve the excellent high gloss. A coating with clear lacquer would etch the effect painting. The only possibility to renew the gloss is to apply a new coat of the effect spray.

5- STORAGE AND SHELF LIFE

10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%).



6- ENVIRONMENT AND LABELLING

Environmentally sound: The products are 100% free of heavy metals. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products comply with the actual labelling regulations according to

Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

7- TECHNICAL PROPERTIES

Basis	: Acrylate copolymeres	
Color	: Chrome, Gold	
Smell	: Solvent	
Degree of gloss	: Not measurable, >100	DIN 67530
Efficiency	: 1.2 m ² * (400 mL)	
Drying time (20 °C and 50% R.H)	: Approx. 10 minutes (Dust-dry) 60 minutes (Dry to touch) Approx. 24 hours (Cured)	
Temperature resistance	: Up to 80°C	

* Depending on consistence and color of the ground.

8-COLOR TABLE

Art No	Color Code
423062	Chrome effect
423192	Gold effect

9- DISCLAIMER

This application-technological information is given to the best of our knowledge. The notes mentioned herein are ,however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. Akkim Sealants & Adhesives is not responsible for any false usage of the product.