



METAL MATT BRONZE EFFECT

1 – DESCRIPTION

Metal Matt Bronze Effect is ideal for handicraft works on wood, metal, glass, cardboard and plants. Bronze Spray is particularly suitable for decorative indoor uses and indispensable for stand constructors, decorators, and flower-arrangers. Metal matt spray is also a good choice for handicraft work at home or in courses and seminar.

2 – PROPERTIES

- High-grade synthetic quality
- Long-term high coverage and filling power
- Excellent adhesion
- Good flow, smooth surface
- Quick-drying (The drying time depends on surrounding temperature, air humidity and thickness of the applied coat).
- Suitable for use on indoor objects
- Resistant to water and common household cleansers.
- Effect of gloss can change by intense rubbing or wiping.

3 - APPLICATIONS

- For handicraft works on wood, metal, glass, cardboard and plants
- Suitable for decorative indoor uses.

4 - INSTRUCTIONS

- The ground has to be clean, dry and free of fat.
- Absorbant surfaces should be primed Universal Primer.
- Mask off areas not to be painted.
- Shake the can vigorously for approx. 3 minutes.
- Test spray at an invisible spot to check colour and compatibility.
- Spray several thin coats from a distance of approx. 25 cm.
- Due to technical reasons it is not possible to conserve the excellent high gloss. A coat of clear lacquer would dissolve the effect lacquer. Just renew the gloss by applying a new coat of metal matt spray.

5- STORAGE AND SHELF LIFE

10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%).



6- ENVIRONMENT AND LABELLING

Environmentally sound: The products are 100% free of heavy metals. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling: All products comply with the actual labelling regulations according to

Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

7- TECHNICAL PROPERTIES

| | | |
|--|--|-----------|
| Basis | : Synthetic Resin | |
| Color | : Bonze, Gold | |
| Smell | : Solvent | |
| Degree of gloss | : at measurement angle 60° high gloss, not measurable, as over 100 | DIN 67530 |
| Efficiency | : approx. 1.2 m ² (400 mL) | |
| Drying time (20 °C and 50% R.H) | : approx. 10 minutes (Dust-dry) 60 minutes (Dry to touch) approx. 24 hours (Cured) | |
| Temperature resistance | : up to 80°C | |

8- COLOR TABLE

| Art No | Color Code |
|--------|--------------------|
| 423086 | Bronze Effect Gold |

9- DISCLAIMER

This application-technological information is given to the best of our knowledge. The notes mentioned herein are ,however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. Akkim Sealants & Adhesives is not responsible for any false usage of the product.